






公差/General tolerances (mm)											D 0.1/10 ±2			
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250		>315	>400	>500
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50



PCB LAYOUT



Note: The A&Z (H) in the name means: A(H) and Z (H).

ITEM	NAME OF PART	MATERIAL	NOTES
2	Pin	Copper alloy	Sn Plated
1	Housing	Thermoplastic	UL94V-0

UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		300/15	/	/
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		320/20	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		4	/	/
间距/Pitch(mm)/线数范围/Poles		5.00/N=02~24P		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

DEGSON MATERIAL: SURFACE/COLOR: MAT NO./REV: - / 00 MAT STATUS: 批量

NAME: 8EDGVC-THR-5.0-XXP-1Y-00A&Z(H)

APPD: 蓝美凡	2023.01.06	NAME			
CHKD: 曹利彬	2023.01.06	DRAWING NO.	200128241	TYPE	CUSTOMER DRAWING
DRFT: 姜民洁	2023.01.06	DRAWING STATUS	已发布	SCALE	5:1
		SHEET	1/1		

REV	ECN	DESCRIPTION	DRFT	DATE
00				

Transfer or duplication of this document as well as the utilization or reproduction of its contents without the written consent of DEGSON is prohibited. All rights reserved for patent.