Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及实用、专利新型和外观专利的所有权利。



PCB LAYOUT

未注公差/General tolerances(mm)														
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°











Note:
The A&Z(H) in the name means:A(H) and Z(H)

ITEM	NAME OF PART	MATERIAL	NOTES
4	Screw	Steel	M3/Zn_plated
3	Cage	Copper alloy	M3/Ni_plated
2	Pin_header	Copper alloy	Sn_plated
1	Housing	Nylon	UL94V-0

	B	C	D
UL 标准/UL Standard:			
额定电压/电流/Rated Voltage(V)/Current(A)	300/30	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	/	III/2	/
额定电压/电流/Rated Voltage(V)/Current(A)	/	1000/3	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	3.5	/
螺丝扭矩/Torque Tightening(N· m/Lb.in)	M3, 0.5/4.43		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG)	26~ 10 / 0.2~ 6.0		
间距/Pitch(mm)/线数范围/Poles	9.52/N= 02~ 24P		
剥线长度/Stripping length(mm)	8~ 9		
使用温度范围/Operating temperature(°C)	-40~ + 105		
符合RoHS环保要求/Conform to RoHS	Yes		

REV	ECN	DESCRIPTION	DRFT	DATE
00			曹心一	2022.12.08

DEGSON

APPD:	David	2022.12.08
CHKD:	David	2022.12.08
DRFT:	曹心一	2022.12.08

A4 mm (inch)

MATERIAL: SURFACE/COLOR:

MAT NO./REV: / 00 MAT STATUS: 批量

NAME: DG636-9.52-XXP-1Y-00A&Z(H)

DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200124055	CUSTOMER DRAWING	被替代	2:1	1/1