

Overview

Product information



Relay base-DSRT05A-3-00A(H)-30020000057

DSRTrelay base,used for1PDTrelay,screw connection

Product advantages

- ☑ Plug-in relay socket
- ☑ Safe isolation between coil and contacts
- ☑ 16A, 1PDTgrade

Product certification

Technical data

Product drawing

3D model

Environmental data

Ambient temperature (storage/transport)	-40 °C ... +85 °C
Ambient temperature (operation)	-20 °C ... 50 °C

Technical data

Rated voltage UN	300V
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm

screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	73.3mm
width	16mm
Depth including bracket	29.5mm

Accessories

Business data

Order number	30020000057
Packing unit	20 SKT
Minimum order quantity	20 SKT
Products weight (without packaging)	27g