

Overview

Product information



DS4-HE-LD60-11040000191

Fuse terminal blocks, connector method: Push-in connector, Fuse type: G / 5 x 20, Glass/ceramic/..., Rated voltage : 60 V, Rated current : 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, Width: 6.2 mm, Color: black, Mounting type: NS35/7.5, NS35/15

Product advantages

- ☑ Fuse terminal blocks.
- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ Snap-on fuse box for easy fuse replacement.
- ☑ Equipped with LED indicator for quick identification of fusing status.
- ☑ Equipped with dual-channel bridge wells, circuit connection testing is more flexible.
- ☑ Equipped with test holes for easy testing of the circuit.

Product certification



Technical data

Product drawing

3D model

□

IEC Electrical parameters

Rated voltage (III / 3)

60V

UL Electrical parameters

Rated voltage

/

Rated current

/

Wiring data

Conductor cross section flexible (ferrule without plastic sleeve)

0.2-4mm²

Conductor cross section flexible (ferrule with plastic sleeve)	0.2-4mm ²
2 flexible conductors with a TWIN ferrule	0.5-1mm ²
Strip length	11~13mm
Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~4mm ²
Conductor cross section solid AWG	24~10

Environmental conditions

Ambient temperature (storage / transport)	-25℃~60℃
Ambient temperature (operation)	-40℃ ~ 105℃ (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated current (III / 3)	6.3A
-------------------------	------

Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Dimension

Height	29.3mm
NS 35/7,5 Height	36.8mm
End plate width	1.5mm
NS 35/15 Height	44.3mm
length	55.6mm
width	6.2mm

Overview

Insulating material group	I
standard test	IEC60947-7-3
Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
fuse	G/5 x 20
Fuse type	Glass/ceramic/...

Accessories

Marker

Top marker	ZB6 / ZS6
Side marker	ZSF6
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
---	---------

Bridge	DFBXX-6.2
End cover	D-DS4-HE

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Business data

Order number	11040000191
Packing unit	100
Minimum order quantity	100
Products weight (without packaging)	9.705