

## Overview

### Product information



### Interface module-DT007-00A(H)-30040000094

32 positions input output module,with indicator light,with screw connector and IDC stitching line,can access 32 positions NPN signal,can be installed on DIN35 rail

### Product advantages

Suitable for 32-point (34/40-bit interface) controller, Screw connection

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Dimension

width	57mm
Height	47mm
length	111mm

### Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

### Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

#### Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	32
Status Display	Yes

#### Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	40
spacing	2.54mm

#### Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm² ... 2.5 mm²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	34
screw thread	M3
Hard wire cross section	1.0 mm² ... 2.5 mm²

Accessories	
Accessories	
Wire harness	DX210-4S-500-00A(H)

Business data	
Order number	30040000094
Packing unit	1
Minimum order quantity	10
Products weight (without packaging)	128