

Overview

Product information



Interface module-DM50-IDC-34-40-4M-00A(H)-30040000093

Mitsubishi PLC dedicated, with indicator light, with screw connector and IDC stitching line, can be installed on DIN35 rail, 40 positions

Product advantages

The signal is clearly marked and the wiring is simple
Screw connection

Product certification

Technical data

Product drawing

3D model

□

Dimension

width	57mm
Height	44mm
length	111mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	32
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	34
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Accessories	
Accessories	
Wire harness	DX210-4S-500-00A(H)

Business data	
Order number	30040000093
Packing unit	1
Minimum order quantity	10
Products weight (without packaging)	128