

Overview

Product information



Interface module-DM50-MDR-20-20-4Y-00A(H)-30040000065

MDR module,input/output module,with screw connectorand MDR connector,can be installed on DIN35 rail,20 positions

Product advantages

20digits to 50digits

1:1 connection

Screw connection

Product certification

Technical data

Product drawing

3D model

Dimension

width	57mm
Height	42mm
length	81mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3

Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	0.5A
Signal points	20
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	MDR connection
Connection volume	1
Number of digits	20
spacing	1.27mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	22
screw thread	M3

Hard wire cross section	1.0 mm² ... 2.5 mm²
-------------------------	---------------------

Accessories

Accessories

Wire harness	DX220-3S-500-00A(H)
--------------	---------------------

Business data

Order number	30040000065
Packing unit	1
Minimum order quantity	10
Products weight (without packaging)	115