

Overview

Product information



Interface module-DM50-DG-8-10-1N-00A(H)-30040000012

8 positions output module, I/O interface module, can access binary or ternary NPN signal, with indicator light, with screw connector, can be installed on DIN35 rail

Product advantages

Quick-plug wiring
Screw connection
Can be connected to 2 or 3 NPN signals
With indicator light

Product certification

Technical data

Product drawing

3D model

□

Dimension

width	57mm
Height	35mm
length	65.5mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
-----------------------	----------

Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	2A
Signal points	8
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	Screw connection
Connection volume	1
Number of digits	10
spacing	5.08mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	0.5mm ² ... 1.5 mm ²
Connectable guide cross section AWG	28-16AWG
Connection meets standards	UL1059
Connection method	Plug screw connection
Connection volume	8
Number of digits	3

screw thread	M2
Hard wire cross section	0.5mm² ... 1.5 mm²

Accessories

Business data

Order number	30040000012
Packing unit	2
Minimum order quantity	10
Products weight (without packaging)	76