

Overview

Product information



Relay module-DM72-RMUS-16-PN-1-4M-00A(H)-30030000103

Subminiature Relay Module, with 20P/40P Horn connector, with relay Socket ,16 relays can be installed, with relay Socket, with indicator light, panasonic relay, PNP or NPN signal can be input (Please contact us for relay replacement)

Product advantages

- ☑ Each signal channel and power supply voltage have LED status indicators
- ☑ Pluggable subminiature relay, with a set of normally open contacts, one-to-one output at the output
- ☑ Freewheeling diode for each signal path
- ☑ Prefabricated cables, plug and play, fast wiring

Product certification

_		
Tec	hnica	l data

Product drawing

3D model

Overview

Installation location	Arbitrary
Number of channels	16
Shell Insulation Materials	PVC/PA66
color	green

Dimension

width	90mm
Height	61mm
length	139mm

Enter technical data

Rated input voltage	24VDC
Input voltage range relative to UN	0.91.1
protected name	Polarity protection
Protection circuits/components	Polarity Protection Diode
Status display/channel	green

Export technical data

contact type	1NO
Maximum switching voltage	240VAC 30VDC
Limit continuous current	5A
Fault monitoring (open circuit/short circuit)	no

output connection data

connection name	output
Connection method	screw connection
Stripping length	6-7mm
thread	M3
connection volume	2
number of digits	11720
Hard conductor cross section	1.0 2.5mm²
Flexible conductor cross section	1.0 2.5mm²
Connectable guide cross section AWG	2812AWG

Enter connection data

connection name	enter
Connection method	IDC/MIL connectors
connection volume	3

number of digits	20/40	
invironmental data		
Ambient temperature (operation)	-20 °C 70 °C	
Ambient temperature (storage / transport)	-20 °C 70 °C	
Standards/Regulations		
Standards/Regulations	IEC61810	
Pollution level	3	

ccessories	
Accessories	

Business data	
Order number	30030000103
Packing unit	2
Minimum order quantity	10
Products weight (without packaging)	300