

Product information		
	10A-GF-0.7	5-92116900005
		le pins,Adapter wire specification0.75mm <sup>2</sup>
Product advantages		
☑High-precision turning process, sta	ble and reliable products	
☑ Gold-plated and silver-plated are a ☑ Comprehensive products, resistant	available, suitable for diffe	erent environmental requirements;
Product certification		,
echnical data		
Product drawing		
Product drawing		
3D model		
Marking		
classification		Contact
Series		10A
Contact type		Crimping contact
versions		
versions Female/Male		Female
		Female
Female/Male		
Female/Male manufacturing technique		
Female/Male manufacturing technique Material characteristics		Turning

itandards		
Connection meets standards	EN 60664-1 IEC 61984	
Technical specification		
Conductor cross sections (mm <sup>2</sup> )	0.75mm <sup>2</sup>	
Conductor cross sections(AWG)	18AWG	
Working current	≤10A	
Contact resistance	≤3mΩ	
Plating Thickness	≥3µ"	
Temperature range	-40°C~+125°C	
Strip length	8mm	
working life-mating cycles	≥500	

## Accessories

Business data	
Order number	92116900005
Packing unit	100
Minimum order quantity	100

Order number	92116900005
Packing unit	100
Minimum order quantity	100
Products weight (without packaging)	0.6592