

## Overview

#### Product information



# D10B-SF-4g-2M20-21010000221

10B Lower base, Four levers, back cover , side entry, double M20 Thread hole

## Product advantages

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;

☑Various installation methods and outlet directions to meet on-site wiring requirements;

 $\ensuremath{\square}$  Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

# Technical data

## Product drawing

3D model

# Marking

| classification | Upper Housing/base |
|----------------|--------------------|
| Series         | В                  |
| Туре           | Surface mount base |
| Specification  | Low structure      |

#### versions

| Dimension            | 10B         |
|----------------------|-------------|
| locking Category     | Double lock |
| Thread specification | 2x M20      |

#### Material characteristics

| Flammability rating           | V-0                      |  |
|-------------------------------|--------------------------|--|
| RoHS                          | conform                  |  |
| Material (upper housing/base) | Die-cast aluminium alloy |  |
| Material(upper housing/base)  | spray                    |  |
| Color (upper housing/base)    | Grey (RAL 7037)          |  |
| Material (seal)               | NBR                      |  |
| Technical specification       |                          |  |
| Limiting temperatures         | -40℃~+125℃               |  |
| IP class                      | IP65                     |  |

| Accessories |  |  |  |
|-------------|--|--|--|
|             |  |  |  |

| Business data                       |             |
|-------------------------------------|-------------|
| Order number                        | 21010000221 |
| Packing unit                        | 100         |
| Minimum order quantity              | 1           |
| Products weight (without packaging) | 189         |