

## Overview

#### **Product information**



# D24B-SE-4g-PG21-21010000095

24BHoods, Four levers, side entry, PG21 Thread hole

## Product advantages

 ${\bf \ensuremath{\square}} {\sf Metal} \ {\sf or} \ {\sf high-strength} \ {\sf plastic} \ {\sf material}, \ {\sf resistant} \ {\sf to} \ {\sf high-strength} \ {\sf mechanical} \ {\sf shock};$ 

☑Various installation methods and outlet directions to meet on-site wiring requirements;

 $\ensuremath{\square}$  Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

## Technical data

## Product drawing

3D model

## Marking

classification	Upper Housing/base
Series	В
Туре	Top housing
Specification	Low structure

#### versions

Dimension	24B
locking Category	Double lock
Wiring method	Side entry
Thread specification	1x PG21

Material characteristics

RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)

## Technical specification

Limiting temperatures	-40°C~+125°C
IP class	IP65

## Accessories

## Business data

Order number	21010000095
Packing unit	100
Minimum order quantity	1
Products weight (without packaging)	240