

Overview

Product information



D10B-TEH-2L-M32-21010000239

10BHoods,double button,top entry,M32 Thread hole

Product advantages

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;

☑Various installation methods and outlet directions to meet on-site wiring requirements;

 $\ensuremath{\square}$ Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

Technical data

Product drawing

3D model

Marking

| classification | Upper Housing/base |
|----------------|--------------------|
| Series | В |
| Туре | Top housing |
| Specification | Lowstructure |

versions

| Dimension | 10B |
|----------------------|-------------|
| locking Category | Double lock |
| Wiring method | Top entry |
| Thread specification | 1x M32 |

Material characteristics

| RoHS | conform |
|-------------------------------|--------------------------|
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey (RAL 7037) |
| Material (lock catch) | Zinc plated |

Technical specification

| Limiting temperatures | -40℃~+125℃ |
|-----------------------|------------|
| IP class | IP65 |

Accessories

Business data

| Buomisso data | |
|-------------------------------------|-------------|
| Order number | 21010000239 |
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 218 |