

	Overview	
Product information		
	Sensor/Actuator Fem	<b>P-FF-SF7003-20030000377</b> ale socket,M12,Coding D,Unshielded,Rear panel hread mounted,90° horizontal pins
Product advantages		
<ul> <li>☑ Sealing optimization, protection level</li> <li>☑ Meet the harsh environment</li> <li>☑ Suitable for various occasions conn</li> <li>☑ Compatible with the international and</li> </ul>	ection technology	products
Product certification		
<b>CSU</b> <sup>®</sup> us ROHS	REACH .9	®
Technical data		
Technical data Product drawing		
Product drawing		
Product drawing 3D model		
Product drawing 3D model		-40℃105℃
Product drawing 3D model • Environmental conditions		-40°C105°C IP67
Product drawing 3D model Environmental conditions Ambient temperature		

Rated current	4A
	250V
Number of potentials	4
Insulation resistance	≥ 100 MΩ
Error-proof coding	D-Code

Overvoltage level	П
Pollution level	3
Connection method	Soldering pin
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Rear board installation

## Material

Flammability rating ,in line with UL94	VO
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon
Standards and specifications	
Standards/specifications	IEC 61076-2-101

Accessories		
Accessories		
Sealing cap	CAP-M12-MP-8003	

Business data	
Order number	20030000377
Packing unit	1
Minimum order quantity	100
Products weight (without packaging)	1