

Overview			
Product information			
	Sensor/Actuator Cab	IP-FF-SR8B01-20030000850 ele,PUR,black,UL20549,Female plug,acodado M12,Coding ng cable end,Cable Cable length:1m	
Product advantages			
 ✓ Sealing optimization, protection level up to IP68 ✓ Meet the harsh environment ✓ Suitable for various occasions connection technology ✓ Compatible with the international and domestic same series products 			
Product certification			
Rohs Reach			
Technical data Product drawing 3D model			
Environmental conditions			
Ambient temperature		-25℃80℃	
IP class		IP68	
General parameters			
		12A	
Rated current		63V	
Number of potentials		4	
Insulation resistance		≥ 100 MΩ	
Error-proof coding		T-Code	

Overvoltage level	III
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon
Standards and specifications	

|--|

Cable

Cable type	PUR Black
Cable type(abbreviation)	PUR
UL AWM form	UL20549
Cross section	1.31mm ²
AWG signal wire	16AWG
Wire structure Signal wire	26/0.254mm ²
Core diameter (including insulation layer)	2.3±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black
Thickness, insulation	0.68mm
Cable outer diameter D	7.8mm
Minimum bend radius ,fixed installation	5*OD

Minimum bend radius ,mobile installation	10*OD
Bending times	4 million times
Bending radius	50.8mm
Cable weight	105.5kg/km
Outer sheath, material	PU
Conductor insulation material	PVC
Conductor material	Tinned copper
Insulation resistance	10ΜΩ
Conductor resistance	Maximum 14.6Ω/km (at 20 °C))
Nominal cable voltage	300V
Cable test voltage	2000∨
Special attributes	Silicone-free
Flame retardant	VW-1
Other protection functions	Anti-UV
Dimension	
Cable length	1m

Accessories		
Accessories		
Sealing cap	CAP-M12-MP-8001	

Business data		
Order number	2003000850	
Packing unit	/	
Minimum order quantity	100	

1