

Overview				
Product information	roduct information			
	voltage (UL) :300V,	rier terminal blocks,Rated current:20A.Rated		
Product advantages				
 Screw connection for worldwide use Fence type wiring structure, stable and reliable connection Solder plate mounting for electrical connection of the device to the PCB 				
Product certification				
Technical data				
Product drawing				
3D model				
•				
Processing notes				
Process		Wave soldering/manual soldering		
Connection capacity				
AWG		22~12AWG		
Torque		0.5N.m		
Electrical parameters UL				
Rated voltage (B)		300V		
Rated voltage (D)		300V		
Rated current (B)		20A		

Rated current (D)	10A		
Electrical parameters IEC			
Defed summer	1000V		
Rated current	32A		
Item properties			
Type of installation	PCB welding		
Pin arrangement	Single row in a straight line		
Connection method	Screw connection		
Screwdriver	slotted-phillips screwdriver		
screw thread	M3		
Pitch	8.25mm		
Number of potentials	2		
Pluggable or not	no		
Number of rows	1		
Material data			

Environmental items	Compliant with REACH/RoHS	
Contact material	Copper alloy	
Contact point metal surface	tin-plated	
Insulation Materials	PA66	
Insulating material group	Ι	
Flammability rating	UL94V-0	
Mechanical tests		
Test Specification	UL1059	
Environmental data		
Ambient temperature (operation)	-40°C~105℃(depending on derating curve)	

Accessories

Accessories

Business data Order number 12020000130 Packing unit 100 Minimum order quantity /

Packing unit	100
Minimum order quantity	/
Products weight (without packaging)	4.7